



All About: Zing First Impression Coating

First Impression Coating is a new breakthrough technology in floor surface protection. It produces an outstanding high gloss that resists soil penetration. For use on all hard surfaces. Can be cut 50/50 with water for double the coverage.

Directions

Note: Area to be coated must be prepared using **Zing Floor Prep**, or perform a complete stripping prior to applying **First Impression Coating**. For best results use a **Microfiber Flat Mop**.



Step 1 - Vacuum or dust mop to remove "Loose Dirt" and Dust.



Step 2 - Apply using straight even strokes. Allow to completely dry before re-coating.



Step 3 - After first coat has completely dried, apply each additional coat in the opposite direction.



Step 4 - Apply **Coating Wear Marks** in high traffic areas for the last 2 coats. Note: Apply up to 4 coats in any 24 hour period. Let Coating cure 24 hours before burnishing.

Benefits

- Buffable
 - transparent
 - Non-Slippery
 - Can be cut 50/50 with water for double the coverage.
 - Applies easily
 - Water based acrylic
 - Works on all floor surfaces
- 3 coats = 5 coats of other finishes

Packaged

4 x 1 gallon case

Coverage

1 gallon covers 2,500 sq. ft.
With Microfiber Flat Mop.
1 gallon makes 2 or 5,000 sq. ft. of coverage.



Specifications

Appearance of Product.....Milky white
 Odor.....Pleasant
 Removability.....Excellent
 Buffability.....Excellent
 Recoatability.....Excellent
 Safety.....Exceeds ASTM safety standards
 Shelf life.....1 year minimum